

ThyssenKrupp Materials (UK) Ltd

LEDs and plastics



White Channel Letters

The chart below breaks down the SloanLED white product line by can depth and Kelvin temperature.

White	Temperature	Desired Can Depth						
		2 inch	3 inch	4 inch	5 inch	6 inch	7 inch	8 inch
V180	6500 K	Optimal	Optimal	Optimal	Requires Testing			
V Series	7200 K, 4200 K	Requires Testing	Optimal	Optimal	Optimal	Acceptable	Acceptable	Acceptable
Apollo	5000 K		Requires Testing	Optimal	Optimal	Optimal	Optimal	Optimal
Great White 4	6500 K			Requires Testing	Optimal	Optimal	Optimal	Optimal
VL Plus Mini	6500 K		Requires Testing	Acceptable	Optimal			
VL Plus Short	6500 K			Requires Testing	Optimal	Requires Testing		
VL Plus Long	6500 K			Requires Testing	Optimal	Acceptable	Requires Testing	

■ Optimal ■ Acceptable ■ Requires Testing

Architectural Border Tubing

Product	Key Attributes	Applications
ColourLINE	Neon inspired look, high brightness, easy to cut in the field, low power consumption	<ul style="list-style-type: none"> Small profile border, perimeter lighting Accent display, exhibit lighting
FlexiBRITE	Flexible tubing, pre-assembled/sealed, easy to cut in the field, easy to bend in the field without heating	<ul style="list-style-type: none"> Free-form shapes, logos, small border lighting Open face channel letters
LEDStripe	Ultra-bright large profile tubing, high impact rigid tubing, daytime colour when non-illuminated	<ul style="list-style-type: none"> Large profile border, perimeter, accent lighting

NEW CONTACTS

New External Contact

cameron.sargeant@thyssenkrupp.com

New Internal Contact

paul.anderson@thyssenkrupp.com

ThyssenKrupp Materials (UK) Ltd

Tel: 0844 846 9573

Fax: 0844 846 9574

www.tkplastics.co.uk

Suppliers of Ooroglas Cast Acrylic, Quinn Extruded Acrylic, Dibond, Dilite, Marlon Polycarbonate Sheet, Forex Classic/Forex Print, Stainless Steel and Aluminium

ThyssenKrupp Materials (UK)



ThyssenKrupp